

CE		
RIKA Innovative Ofentechnik GmbH AT-4563 Micheldorf, Müllerviertel 20 17 60-CPR-07.2013		
EN13240:2001/A2:2004/AC:2007		
Notified Body: 1746		
Intended use: Space heating in residential buildings without possible supply of hot water		
Name: PARO SCHEITHOLZ		
Description: space heating appliances fired by wood logs - system 3		
Height		1132 mm
Width		788/9519 mm
Depth		506 mm
Fire safety		pass
Safety distance to combustible material	rear	100 mm
	sides	100 mm
	top	500 mm
	front	800 mm
	floor	12 mm
Emission of combustion products		pass
CO-Emmision at nominal heat output		< 0,12 %
CO-Emmision at nominal heat output		< 1,25 g/Nm ³
Release of dangerous substances		NPD
Surface temperature		pass
Electrical safety		pass (*)
Cleanability		pass
Durability		pass
Mechanical resistance (to carry chimney)		NPD
Maximum operating pressure		not applicable
Flue gas temperature at the measuring section at nominal heat output		152,5 °C
Flue gas temperature outlet at nominal heat output		183 °C
Thermal output		pass
Nominal- / part load heat output	8,0 kW	4,0 kW
Nominal- / part load space heat output	8,0 kW	4,0 kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency		pass
Nominal- / part load Efficiency	91%	90,7 %
recommended fuel type	wood logs	
Suitability for installation to a shared flue system		yes
Emission (addition)		
CO wood logs PM wood logs OGC wood logs NO _x wood logs	g/Nm ³	< 1,25
	g/Nm ³	< 0,04
	g/Nm ³	< 0,12
	g/Nm ³	< 0,20
Pleas read manufacturer´s operating instructions carefully before installing and using the appliance!		

(*) only for models with RIKATRONIC

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

RIKA®

Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertel 20
Tel.: +43 (0)7582/686-14, Fax DW: -43
www.rika.at



Name and function

Micheldorf, 15.11.2022

Place and date of issue