

<div>CE</div>		
RIKA Innovative Ofentechnik GmbH AT-4563 Micheldorf, Müllerviertel 20 18 6306-CPR-07.2013		
EN13240:2001/A2:2004/AC:2007		
Notified Body:	1746	
Intended use:	Space heating in residential buildings without possible supply of hot water	
Name:	BACK 6 kW	
Description:	space heating appliances fired by wood logs - system 3	
Height	1336 mm	
Width	505 mm	
Depth	435 mm	
Fire safety	pass	
Safety distance to combustible material	rear	100 mm
	sides	100 mm
	top	500 mm
	front	800 mm
	floor	0 mm
Emission of combustion products	pass	
CO-Emission at nominal heat output	< 0,12 %	
CO-Emission at nominal heat output	< 1,25 g/Nm ³	
Release of dangerous substances	NPD	
Surface temperature	pass	
Electrical safety	pass (*)	
Cleanability	pass	
Durability	pass	
Mechanical resistance (to carry chimney)	NPD	
Maximum operating pressure	not applicable	
Flue gas temperature at the measuring section at nominal heat output	201,6 °C	
Flue gas temperature outlet at nominal heat output	241,9 °C	
Thermal output	pass	
Nominal- / part load heat output	6,0 kW	- kW
Nominal- / part load space heat output	6,0 kW	- kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency	pass	
Nominal- / part load Efficiency	84,6 %	- %
recommended fuel type	wood logs	
Suitability for installation to a shared flue system	yes	
Emission (addition)		
CO wood logs	g/Nm ³	< 1,25
PM wood logs	g/Nm ³	< 0,04
OGC wood logs	g/Nm ³	< 0,12
NO _x wood logs	g/Nm ³	< 0,20
Pleas read manufacturer's operating instructions carefully before installing and using the appliance!		

(*) only for models with RIKATRONIC



Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertel 20
Tel. +43 (0)7562/686-14, Fax DW. -43
www.rika.at

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 15.11.2022

Place and date of issue