

# DECLARATION OF PERFORMANCE

according to Regulation (EU) 305/2011  
62-CPR-07.2013

|                                                                               |                                                                                                                                                                                                                                                 |                                                                           |     |        |
|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|-----|--------|
| 1.)                                                                           | Type                                                                                                                                                                                                                                            | COOK                                                                      |     |        |
| 2.)                                                                           | Use of the construction product                                                                                                                                                                                                                 | room heater in residential buildings                                      |     |        |
| 3.)                                                                           | Manufacturers                                                                                                                                                                                                                                   | RIKA Innovative Ofentechnik GmbH<br>Müllerviertel 20<br>A-4563 Micheldorf |     |        |
| 4.)                                                                           | Authorised representative                                                                                                                                                                                                                       | Andreas Bloderer                                                          |     |        |
| 5.)                                                                           | Systems of assessment and verification of constancy of performance of the construction product                                                                                                                                                  | System 3                                                                  |     |        |
| 6.)                                                                           | The notified testing laboratory has carried out the initial test according to system 3. Notified body no.                                                                                                                                       | 1746                                                                      |     |        |
|                                                                               | Test report no.                                                                                                                                                                                                                                 | PL-25026-23-P                                                             |     |        |
| 7.)                                                                           | Harmonized technical specification                                                                                                                                                                                                              | EN 16510-2-1:2022                                                         |     |        |
| 8.)                                                                           | <b>Essential characteristics</b>                                                                                                                                                                                                                |                                                                           |     |        |
|                                                                               | <b>Mechanical strength and stability</b>                                                                                                                                                                                                        |                                                                           |     |        |
|                                                                               | Carrying capacity                                                                                                                                                                                                                               | 25 kg                                                                     |     |        |
|                                                                               | <b>Fire protection</b>                                                                                                                                                                                                                          |                                                                           |     |        |
|                                                                               | Safety distance to combustible material<br>Minimum distance                                                                                                                                                                                     | d <sub>R</sub> = rear                                                     |     | 100 mm |
|                                                                               |                                                                                                                                                                                                                                                 | d <sub>S</sub> = side                                                     |     | 100 mm |
|                                                                               |                                                                                                                                                                                                                                                 | d <sub>C</sub> = ceiling                                                  |     | 500 mm |
|                                                                               |                                                                                                                                                                                                                                                 | d <sub>P</sub> = to adjacent combustible materials (e.g. furniture)       |     | 800 mm |
|                                                                               |                                                                                                                                                                                                                                                 | d <sub>F</sub> = floor in front                                           |     | 0 mm   |
|                                                                               |                                                                                                                                                                                                                                                 | d <sub>L</sub> = side radiation area                                      |     | 0 mm   |
|                                                                               |                                                                                                                                                                                                                                                 | d <sub>B</sub> = bottom                                                   |     | 0 mm   |
|                                                                               |                                                                                                                                                                                                                                                 | Material type and thickness of the protective insulation material         |     | NPD    |
|                                                                               | <b>Hygiene, health, and environmental protection</b>                                                                                                                                                                                            |                                                                           |     |        |
|                                                                               | <b>Emissions at nominal heat output at 13% O2</b>                                                                                                                                                                                               |                                                                           |     |        |
|                                                                               | Carbon monoxide (CO)                                                                                                                                                                                                                            | 1142 mg/Nm³                                                               |     |        |
|                                                                               | Nitrogen (NOx)                                                                                                                                                                                                                                  | 96 mg/Nm³                                                                 |     |        |
|                                                                               | Organic gaseous carbon (OGC)                                                                                                                                                                                                                    | 44 mg/Nm³                                                                 |     |        |
|                                                                               | Dust (PM)                                                                                                                                                                                                                                       | 14 mg/Nm³                                                                 |     |        |
|                                                                               | <b>Emissions at reduced heat output at 13% O2</b>                                                                                                                                                                                               |                                                                           |     |        |
|                                                                               | Carbon monoxide (CO)                                                                                                                                                                                                                            | 1293 mg/Nm³                                                               |     |        |
|                                                                               | Nitrogen (NOx)                                                                                                                                                                                                                                  | 103 mg/Nm³                                                                |     |        |
|                                                                               | Organic gaseous carbon (OGC)                                                                                                                                                                                                                    | 65 mg/Nm³                                                                 |     |        |
|                                                                               | Dust (PM)                                                                                                                                                                                                                                       | 12 mg/Nm³                                                                 |     |        |
| <b>Safety and accessibility during use</b>                                    |                                                                                                                                                                                                                                                 |                                                                           |     |        |
| <b>Data on installation on a chimney at nominal heat output</b>               |                                                                                                                                                                                                                                                 |                                                                           |     |        |
| Temperature at the exhaust pipe                                               | 235 °C                                                                                                                                                                                                                                          |                                                                           |     |        |
| Minimum delivery pressure                                                     | 12 Pa                                                                                                                                                                                                                                           |                                                                           |     |        |
| Exhaust gas mass flow                                                         | 5,2 g/s                                                                                                                                                                                                                                         |                                                                           |     |        |
| <b>Data on installation on a chimney at reduced heat output</b>               |                                                                                                                                                                                                                                                 |                                                                           |     |        |
| Temperature at the exhaust pipe                                               | 198 °C                                                                                                                                                                                                                                          |                                                                           |     |        |
| Minimum delivery pressure                                                     | 11 Pa                                                                                                                                                                                                                                           |                                                                           |     |        |
| Exhaust gas mass flow                                                         | 5,4 g/s                                                                                                                                                                                                                                         |                                                                           |     |        |
| <b>Data on installation on a chimney with regard to fire safety</b>           |                                                                                                                                                                                                                                                 |                                                                           |     |        |
| Fire safety for installation on the chimney                                   | T400G                                                                                                                                                                                                                                           |                                                                           |     |        |
| <b>Energy savings and thermal insulation</b>                                  |                                                                                                                                                                                                                                                 |                                                                           |     |        |
| <b>Heat output and energy efficiency of the device at nominal heat output</b> |                                                                                                                                                                                                                                                 |                                                                           |     |        |
| Space heating capacity                                                        | 6,0 kW                                                                                                                                                                                                                                          |                                                                           |     |        |
| Water heating capacity                                                        | NPD                                                                                                                                                                                                                                             |                                                                           |     |        |
| Efficiency                                                                    | 84,2 %                                                                                                                                                                                                                                          |                                                                           |     |        |
| <b>Heat output and energy efficiency of the device at reduced heat output</b> |                                                                                                                                                                                                                                                 |                                                                           |     |        |
| Space heating capacity                                                        | 3,0 kW                                                                                                                                                                                                                                          |                                                                           |     |        |
| Water heating capacity                                                        | NPD                                                                                                                                                                                                                                             |                                                                           |     |        |
| Efficiency                                                                    | 85,5 %                                                                                                                                                                                                                                          |                                                                           |     |        |
| <b>Space heating efficiency</b>                                               |                                                                                                                                                                                                                                                 |                                                                           |     |        |
| Annual space heating efficiency at nominal heat output                        | 74 %                                                                                                                                                                                                                                            |                                                                           |     |        |
| Energy efficiency                                                             | Energy-Efficiency-Index (EEI)                                                                                                                                                                                                                   |                                                                           | 112 |        |
|                                                                               | Energy-Efficiency-Class                                                                                                                                                                                                                         |                                                                           | A+  |        |
| Power consumption at nominal heat output                                      | - kW                                                                                                                                                                                                                                            |                                                                           |     |        |
| Power consumption at reduced heat output                                      | - kW                                                                                                                                                                                                                                            |                                                                           |     |        |
| Power consumption in standby mode                                             | kW                                                                                                                                                                                                                                              |                                                                           |     |        |
| <b>Sustainable use of natural resources</b>                                   |                                                                                                                                                                                                                                                 |                                                                           |     |        |
| Ecological sustainability                                                     | NPD                                                                                                                                                                                                                                             |                                                                           |     |        |
| 9.)                                                                           | The performance of the above product corresponds to the declared performance/performances. The above-mentioned manufacturer is solely responsible for preparing the declaration of performance in accordance with Regulation (EU) No. 305/2011. |                                                                           |     |        |

Signed on behalf of the manufacturer

Andreas Bloderer / product management  
Micheldorf, 26.01.2026



Innovative Ofentechnik GmbH  
A-4563 Micheldorf, Müllerviertel 20  
Tel.: +43 (0)7582/686-14, Fax DW -43  
www.rika.at

*Andreas Bloderer*