

# DECLARATION OF PERFORMANCE

according to Regulation (EU) 305/2011  
66-CPR-07.2013

1.)	Type	COSMO		
2.)	Use of the construction product	room heater in residential buildings		
3.)	Manufacturers	RIKA Innovative Ofentechnik GmbH Müllerviertel 20 A-4563 Micheldorf		
4.)	Authorised representative	Andreas Bloderer		
5.)	Systems of assessment and verification of constancy of performance of the construction product	System 3		
6.)	The notified testing laboratory has carried out the initial test according to system 3. Notified body no.	1746		
	Test report no.	PL-25026-05-P		
7.)	Harmonized technical spezifikation	EN16510-1:2022; EN 16510-2-6:2022		
8.)	<b>Essential characteristics</b>			
	<b>Mechanical strength and stability</b>			
	Carrying capacity	25 kg		
	<b>Fire protection</b>			
	Safety distance to combustible material Minimum distance	d <sub>R</sub> = rear	100 mm	
		d <sub>S</sub> = side	100 mm	
		d <sub>C</sub> = ceiling	500 mm	
		d <sub>P</sub> = to adjacent combustible materials (e.g. furniture)	800 mm	
		d <sub>F</sub> = floor in front	0 mm	
		d <sub>L</sub> = side radiation area	0 mm	
		d <sub>B</sub> = bottom	0 mm	
		Material type and thickness of the protective insulation material		NPD
	<b>Hygiene, health, and environmental protection</b>			
	<b>Emissions at nominal heat output at 13% O2</b>			
	Carbon monoxide (CO)	117 mg/Nm³		
	Nitrogen (NOx)	126 mg/Nm³		
	Organic gaseous carbon (OGC)	4 mg/Nm³		
	Dust (PM)	19 mg/Nm³		
	<b>Emissions at reduced heat output at 13% O2</b>			
	Carbon monoxide (CO)	305 mg/Nm³		
	Nitrogen (NOx)	115 mg/Nm³		
	Organic gaseous carbon (OGC)	7 mg/Nm³		
	Dust (PM)	51 mg/Nm³		
<b>Safety and accessibility during use</b>				
<b>Data on installation on a chimney at nominal heat output</b>				
Temperature at the exhaust pipe	193 °C			
Minimum delivery pressure	12 Pa			
Exhaust gas mass flow	4,1 g/s			
<b>Data on installation on a chimney at reduced heat output</b>				
Temperature at the exhaust pipe	110 °C			
Minimum delivery pressure	10 Pa			
Exhaust gas mass flow	3,1 g/s			
<b>Data on installation on a chimney with regard to fire safety</b>				
Fire safety for installation on the chimney	T200G			
<b>Energy savings and thermal insulation</b>				
<b>Heat output and energy efficiency of the device at nominal heat output</b>				
Space heating capacity	6,0 kW			
Water heating capacity	NPD			
Efficiency	90,7 %			
<b>Heat output and energy efficiency of the device at reduced heat output</b>				
Space heating capacity	2,5 kW			
Water heating capacity	NPD			
Efficiency	91,1 %			
<b>Space heating efficiency</b>				
Annual space heating efficiency at nominal heat output	80 %			
Energy efficiency	Energy-Efficiency-Index (EEI)		121	
	Energy-Efficiency-Class		A+	
Power consumption at nominal heat output	0,01 kW			
Power consumption at reduced heat output	0,01 kW			
Power consumption in standby mode	0,003 kW			
<b>Sustainable use of natural resources</b>				
Ecological sustainability	NPD			
9.)	The performance of the above product corresponds to the declared performance/performances. The above-mentioned manufacturer is solely responsible for preparing the declaration of performance in accordance with Regulation (EU) No. 305/2011.			

Signed on behalf of the manufacturer

Andreas Bloderer / product management  
Micheldorf, 13.11.2025



Innovative Ofentechnik GmbH  
A-4563 Micheldorf, Müllerviertel 20  
Tel.: +43 (0)7582/686-14, Fax DW -43  
www.rika.at

*Andreas Bloderer*