

		
RIKA Innovative Ofentechnik GmbH AT-4563 Micheldorf, Müllerviertel 20		
101-CPR-07.2013		
EN13240:2001/A2:2004/AC:2007 Notified Body: 1746 Intended use: Space heating in residential buildings without possible supply of hot water Name: FOX III Description: space heating appliances fired by wood logs - system 3		
Height	1090 mm	
Width	550 mm	
Depth	460 mm	
Fire safety	pass	
Safety distance to combustible material	rear	100 mm
	sides	100 mm
	top	750 mm
	front	800 mm
	floor	0 mm
Emission of combustion products	pass	
CO-Emission at nominal heat output	< 0,12 %	
CO-Emission at nominal heat output	< 1,25 g/Nm ³	
Release of dangerous substances	NPD	
Surface temperature	pass	
Electrical safety	pass (*)	
Cleanability	pass	
Durability	pass	
Mechanical resistance (to carry chimney)	NPD	
Maximum operating pressure	not applicable	
Flue gas temperature at the measuring section at nominal heat output	~ 200 °C	
Flue gas temperature outlet at nominal heat output	~ 220 °C	
Thermal output	pass	
Nominal- / part load heat output	8,0 kW	4,0 kW
Nominal- / part load space heat output	8,0 kW	4,0 kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency	pass	
Nominal- / part load Efficiency	>=80 %	>=80 %
recommended fuel type	wood logs	
Suitability for installation to a shared flue system	yes	
Emission (addition)		
CO wood logs	g/Nm ³	< 1,25
PM wood logs	g/Nm ³	< 0,04
OGC wood logs	g/Nm ³	< 0,12
NO _x wood logs	g/Nm ³	< 0,20
Pleas read manufacturer's operating instructions carefully before installing and using the appliance!		

(*) only for models with RIKATRONIC



Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 04.06.2025

Place and date of issue