

TECHNICAL DOCUMENTATION

according to commission regulation (EU) 2015/1185 und 2015/1186 Ecodesign

Contact details of the manufacturer

Manufacturer:	RIKA Innovative Ofentechnik GmbH
Contact:	Andreas Bloderer
Address:	Müllerviertel 20
	4563 Micheldorf
	Austria

Details of the device

Model Identifier:	FOX III 6 kW
Equivalent models:	-
Notified body:	Technische Universität Wien, Getreidemarkt 9/166, 1060 Wien, Austria
Notified body no.:	1746
Test report no.:	n.A.
Applied harmonised standards:	EN 16510-2-1:2022
Other applied standards/technical specifications:	-
Indirect heating functionality:	Nein
Direct heat output:	6,0 kW
Indirect heat output:	-

Characteristics when operating with the preferred fuel

Seasonal space heating energy efficiency ηs :	>=70 %
Seasonal space heating energy efficiency RIKATRONIC ηs:	-
Energy Efficiency Index:	>=107 - <130
Energy Efficiency Index RIKATRONIC:	-

Special precautions for assembly, installation or maintenance

 $\label{thm:combustible} Fire \ protection \ and \ safety \ distances \ such \ as \ distances \ to \ combustible \ building \ materials \ must \ be \ observed!$

An adequate supply of combustion air for the appliance must be guaranteed at all times. Air-suction systems can interfere with the combustion air supply!

The flue gas values of the appliance must be observed for the chimney dimensioning!

Characteristics when operating exclusively with the preferred fuel

Heat output							
Nominal heat output	P _{nom}	6,0	kW				
Minimum heat output	P_{min}	4,0	kW				
Useful efficiency							
Useful efficiency at nominal heat output	$\eta_{\text{th,nom}}$	>=80	%				
Useful efficiency at minimum heat output	$\eta_{\text{th,min}}$	>=80	%				
Auxiliary electricity consumption*							
At nominal heat output	el _{max}	n.A.	kW				
At minimum heat output	el_{min}	n.A.	kW				
In standby mode	el _{SB}	n.A.	kW				
Permanent pilot flame power requirement							
Pilot flame power requirement	P _{pilot}	n.A.	kW				

*RIKATRONIC

Type of heat output/room temperature control	
single stage heat output, no room temperature control	Yes
two or more manual stages, no room temperature control (**)	No
with mechanic thermostat room temperature control (**)	No
with electronic room temperature control (**)	No
with electronic room temperature control plus day timer (**)	No
with electronic room temperature control plus week timer (**)	No
Room temperature control with presence detection (**)	No
Room temperature control with open window detection (**)	No
with remote control options (**)	No

Details of the fuel

Fuel	Preferred fuel:	Other suitable fuel:	η _s [%]	Space heating emissions at nominal heat output (*)				Space heating emissions at minimum heat output (*)(**)			
				PM	OGC	CO (13% O	NOx	PM ,	OGC	CO 3 (13% O	NOx
Wood logs, moisture content ≤ 25 %	Yes	No	>=70	<=40	<=120		<=200		<=120	<=1250	
Wood logs RIKATRONIC, moisture content ≤ 25 %	No	No	-	-	-	-	-	-	-	-	1
Compressed wood, moisture content < 12 %	No	No	-	-	-	-	-	-	-	-	-
Other woody biomass	No	No	-	-	-	-	-	-	-	-	-
Non-woody biomass	No	No	-	-	-	-	-	-	-	-	-
Anthracite and dry steam coal	No	No	-	-	-	-	-	-	-	-	-
Hard coke	No	No	-	-	-	-	-	-	-	-	-
Low temperature coke	No	No	-	-	-	-	-	-	-	-	
Bituminous coal	No	No	-	-	1	1	-	-	-	-	1
Lignite briquettes	No	No	-	-	1	1	-	-	-	-	-
Peat briquettes	No	No	-	-	-	-	-	-	-	-	-
Blended fossil fuel briquettes	No	No	-	-	-	-	-	-	-	-	1
Other fossil fuel	No	No	-	-	-	-	-	-	-	-	-
Blended biomass and fossil fuel briquettes	No	No	-	-	-	-	-	-	-	-	-
Other blend of biomass and solid fuel	No	No	-	-	-	-	-	-	-	-	-

(*) PM = dust, OGC = gaseous organic compounds, CO = carbon monoxide, NOx = nitrous gases (**) Only required when applying correction factors F(2) or F(3)

Signed for and on behalf of the manufacturer by: Andreas Bloderer / product management

Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertel 20
Tel: +43 (0)7582/86-14, Fax DW: -43

ALBUL

Micheldorf, 04.06.2025