



26

RIKA Innovative Ofentechnik GmbH
AT-4563 Micheldorf, Müllerviertel 20

regarding EN 16510-2-6:2022 under regulation (EU) 305/2011

DoP: 10106-CPR-07.2013
Notified Body: 1746
Intended use: Space heating in residential buildings without possible supply of hot water
Name: FOX III RIKAir 6kW

IMPORTANT ASPECTS**MECHANICAL STRENGTH AND STABILITY**

Carrying capacity 25 kg

FIRE SAFETY

Safety distance to combustible material	d_R = from the back to combustible materials	200 mm
	d_S = from the sides to flammable materials	200 mm
	d_C = from the top to flammable materials in the ceiling	500 mm
	d_F = from the front to flammable materials	800 mm
	d_L = from the front to flammable materials in the lower front radiation area	0 mm
	d_L = from the front to flammable materials in the lateral front radiation area	0 mm
	d_B = below the floor (without feet) to combustible materials	0 mm

HYGIENE, HEALTH AND ENVIRONMENTAL PROTECTION

Emissions at nominal heat output (based on 13% O ₂)	CO	921 mg/Nm ³
	NOX	108 mg/Nm ³
	OGC	41 mg/Nm ³
	PM	17 mg/Nm ³
Emissions at reduced heat output (based on 13% O ₂)	CO	- mg/Nm ³
	NOX	- mg/Nm ³
	OGC	- mg/Nm ³
	PM	- mg/Nm ³

SAFETY AND ACCESSIBILITY DURING USE

Data for installation on a chimney at nominal heat output	Temperature at the flue gas connection	260,0 °C
	Minimum conveying pressure	12 Pa
	Flue gas mass flow	5,8 g/S
Data for installation on a chimney at reduced heat output	Temperature at the flue gas connection	- °C
	Minimum conveying pressure	- Pa
	Flue gas mass flow	- g/S
Data for installation on a chimney regarding fire safety	Class	T400G

ENERGY SAVINGS AND THERMAL INSULATION

Heat output and energy efficiency of the appliance at nominal heat output	Room heat output	6,0 kw
	Efficiency	81,8 %
Heat output and energy efficiency of the appliance at reduced heat output	Room heat output	- kw
	Efficiency	- %
Space heating efficiency	Annual space heating efficiency at nominal heat output	72 %
	Energy Efficiency Index (EEI)	108
	Energy efficiency class	A+
	Power consumption at nominal heat output	0,003 kw
	Power consumption at partial load heat output	0,003 kw
	Power consumption in standby mode	0,002 kw

Please read manufacturer's operating instructions carefully before installing



Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertel 20
Tel.: +43 (0)7582/686-14, Fax DW: -43

www.rika.at

Micheldorf, 22.04.2026

Place and date of issue