

RIKA Innovative Ofentechnik GmbH AT-4563 Micheldorf, Müllerviertel 20

18

1506-CPR-07.2013

EN13240:2001/A2:2004/AC:200	113240-2001	/A2·2004/	/AC-2007
-----------------------------	-------------	-----------	----------

Notified Body: 1746

Intended use: Space heating in residential buildings without

possible supply of hot water

Name: IMPOSA 6 kW / IMPOSA RIKATRONIC3 6 kW

Descriptioin: space heating appliances fired by wood logs - system 3

Height		1193 mm
Width		578 mm
Depth		516 mm
Fire safety		pass
Safety distance to combustible material	rear	200 mm
	sides	200 mm
	top	500 mm
	front	800 mm
	floor	0 mm
Emission of combustion products		pass
CO-Emmision at nominal heat output		< 0,12 %
CO-Emmision at nominal heat output		< 1,25 g/Nm ³
Release of dangerous substances	NPD	
Surface temperature	pass	
Electrical safety		pass (*)
Cleanability		pass
Durability		pass
Mechanical resistance (to carry chimney)		NPD
Maximum operating pressure	not applicable	
Flue gas temperature	214,6 °C	
at the measuring section at nominal heat output		21.,0 0
Flue gas temperature	257,5 °C	
outlet at nominal heat output		207,5 0
Thermal output		pass
Nominal- / part load heat output	6,0 kW	- kW
Nominal- / part load space heat output	6,0 kW	- kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency		pass
Nominal- / part load Efficiency	81,7 %	- %
recommended fuel type	W	ood logs
Suitability for installation to a shared flue system		yes
Emission (addition)		
CO wood logs	g/Nm³	< 1,25
PM wood logs	g/Nm ³	< 0,04
OGC wood logs	g/Nm³	< 0,12
NO _v wood logs	g/Nm ³	< 0,20

and using the appliance!
(*) only for models with RIKATRONIC

Innovative Ofentechnik Grabh A-4563 Micheldorf, Müllenviertel 20 Tel: +43 (07582/686-14, Fox DW: -43 www.riko.at

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 15.11.2022

Place and date of issue