



RIKA Innovative Ofentechnik GmbH  
AT-4563 Micheldorf, Müllerviertel 20  
17  
65-CPR-07.2013

EN13240:2001/A2:2004/AC:2007

**Notified Body:** 1746

**Intended use:** Space heating in residential buildings without possible supply of hot water

**Name:** LAVITA

**Description:** space heating appliances fired by wood logs - system 3

<b>Height</b>	1156 mm
---------------	---------

<b>Width</b>	578 mm
--------------	--------

<b>Depth</b>	471 mm
--------------	--------

<b>Fire safety</b>	pass
--------------------	------

Safety distance to combustible material	rear	200 mm
	sides	200 mm
	top	500 mm
	front	800 mm
	floor	0 mm

<b>Emission of combustion products</b>	pass
--	------

CO-Emission at nominal heat output	< 0,12 %
------------------------------------	----------

CO-Emission at nominal heat output	< 1,25 g/Nm <sup>3</sup>
------------------------------------	--------------------------

<b>Release of dangerous substances</b>	NPD
--	-----

<b>Surface temperature</b>	pass
----------------------------	------

<b>Electrical safety</b>	pass (*)
--------------------------	----------

<b>Cleanability</b>	pass
---------------------	------

<b>Durability</b>	pass
-------------------	------

<b>Mechanical resistance (to carry chimney)</b>	NPD
---	-----

<b>Maximum operating pressure</b>	not applicable
-----------------------------------	----------------

<b>Flue gas temperature at the measuring section at nominal heat output</b>	187,7 °C
---	----------

<b>Flue gas temperature outlet at nominal heat output</b>	225,2 °C
---	----------

<b>Thermal output</b>	pass
-----------------------	------

Nominal- / part load heat output	10,0 kW	5,0 kW
----------------------------------	---------	--------

Nominal- / part load space heat output	10,0 kW	5,0 kW
--	---------	--------

Nominal- / part load water heat get output folder path	not applicable	not applicable
--	----------------	----------------

<b>Efficiency</b>	pass
-------------------	------

Nominal- / part load Efficiency	86%	87,4 %
---------------------------------	-----	--------

<b>recommended fuel type</b>	wood logs
------------------------------	-----------

<b>Suitability for installation to a shared flue system</b>	yes
---	-----

Emission (addition)

CO wood logs	g/Nm <sup>3</sup>	< 1,25
--------------	-------------------	--------

PM wood logs	g/Nm <sup>3</sup>	< 0,04
--------------	-------------------	--------

OGC wood logs	g/Nm <sup>3</sup>	< 0,12
---------------	-------------------	--------

NO <sub>x</sub> wood logs	g/Nm <sup>3</sup>	< 0,20
---------------------------	-------------------	--------

**Please read manufacturer's operating instructions carefully before installing and using the appliance!**

(\*) only for models with RIKATRONIC



Innovative Ofentechnik GmbH  
A-4563 Micheldorf, Müllerviertel 20  
Tel. +43 (0)7562/686-14, Fax DW. -43  
www.rika.at

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 15.11.2022

Place and date of issue