

# Data sheet


## LIVO



Technical data		
Heating power range	[kW]	2,5 - 6
Nominal heat output	[kW]	6
Fresh air demand	[m³/h]	13
Room heating capacity (depending on house insulation)	[m³]	50 - 160
Fuel consumption	[kg/h]	0,6 - 1,3
Pellet container capacity*	[l/kg]	31/~20
Electric supply	[V]/[Hz]	230/50
Average electrical input	[W]	20
Fuse	[A]	2,5
Efficiency	[%]	92,3
Energy efficiency class		A+
Chimney draft requirement	[Pa]	3

\*The capacity in kg may deviate due to different pellet bulk densities.


### Characteristics



Balanced flue



Touch display



USB



Energy efficiency



Quiet


### Accessories



RIKA firenet



RIKA Voice




Fresh air floor connection



Room sensor

## Dimensions, weight and connection



### Weight

Weight with steelshell	[kg]	~120
------------------------	------	------

### Dimensions

Height	[mm]	1020
Width	[mm]	482
Corpus depth	[mm]	513
Firing chamber [WxHxD]	[mm]	210x400x200

### Flue pipe connection

Flue pipe outlet	[mm]	100
Original angle pipe connection height	[mm]	-
Original angle pipe total depth	[mm]	-
Original angle pipe distance to rear wall	[mm]	-
Depth from rear wall to middle of flue pipe	[mm]	-
Original angle pipe side distance	[mm]	-
Rear connection height	[mm]	160
Rear connection side distance	[mm]	169

### Fresh air connection

Diameter	[mm]	50
Connection height	[mm]	276
Side distance	[mm]	170
Floor connection side distance	[mm]	214
Floor connection depth	[mm]	143

## Safety distances

### Note

- To non-combustible objects  
 $a > 40 \text{ cm}$   $b > 10 \text{ cm}$
- To combustible objects and reinforced concrete load-bearing walls  
 $a > 80 \text{ cm}$   $b > 10 \text{ cm}$

