



DoP:	1606-CPR-07.2013
Notified Body:	1746
Intended use:	Space heating in residential buildings without possible supply of hot water
Name:	NEX R4 6 kW

IMPORTANT ASPECTS**MECHANICAL STRENGTH AND STABILITY**

Carrying capacity	25 kg
-------------------	-------

FIRE SAFETY

Safety distance to combustible material	d_R = from the back to combustible materials	100 mm
	d_S = from the sides to flammable materials	100 mm
	d_C = from the top to flammable materials in the ceiling	500 mm
	d_P = from the front to flammable materials	800 mm
	d_F = from the front to flammable materials in the lower front radiation area	0 mm
	d_L = from the front to flammable materials in the lateral front radiation area	0 mm
	d_B = below the floor (without feet) to combustible materials	0 mm

HYGIENE, HEALTH AND ENVIRONMENTAL PROTECTION

Emissions at nominal heat output (based on 13% O ₂)	CO	1181 mg/Nm ³
	NOX	114 mg/Nm ³
	OGC	65 mg/Nm ³
	PM	25 mg/Nm ³
Emissions at reduced heat output (based on 13% O ₂)	CO	- mg/Nm ³
	NOX	- mg/Nm ³
	OGC	- mg/Nm ³
	PM	- mg/Nm ³

SAFETY AND ACCESSIBILITY DURING USE

Data for installation on a chimney at nominal heat output	Temperature at the flue gas connection	313,0 °C
	Minimum conveying pressure	12 Pa
	Flue gas mass flow	7,1 g/S
Data for installation on a chimney at reduced heat output	Temperature at the flue gas connection	- °C
	Minimum conveying pressure	- Pa
	Flue gas mass flow	- g/S
Data for installation on a chimney regarding fire safety	Class	-

ENERGY SAVINGS AND THERMAL INSULATION

Heat output and energy efficiency of the appliance at nominal heat output	Room heat output	6,0 kw
	Efficiency	76,6 %
Heat output and energy efficiency of the appliance at reduced heat output	Room heat output	- kw
	Efficiency	- %
Space heating efficiency	Annual space heating efficiency at nominal heat output	66 %
	Energy Efficiency Index (EEI)	101
	Energy efficiency class	A
	Power consumption at nominal heat output	0,003 kw
	Power consumption at partial load heat output	0,003 kw
	Power consumption in standby mode	0,002 kw

Please read manufacturer's operating instructions carefully before installing

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 20.03.2026

Place and date of issue