

DECLARATION OF PERFORMANCE

according to Regulation (EU) 305/2011
16-CPR-07.2013

1.)	Type	NEX		
2.)	Use of the construction product	room heater in residential buildings		
3.)	Manufacturers	RIKA Innovative Ofentechnik GmbH Müllerviertel 20 A-4563 Micheldorf		
4.)	Authorised representative	Andreas Bloderer		
5.)	Systems of assessment and verification of constancy of performance of the construction product	System 3		
6.)	The notified testing laboratory has carried out the initial test according to system 3. Notified body no.	1746		
	Test report no.	PL-25026-37-P		
7.)	Harmonized technical specification	EN 16510-2-1:2022		
8.)	Essential characteristics			
	Mechanical strength and stability			
	Carrying capacity	25 kg		
	Fire protection			
	Safety distance to combustible material Minimum distance	d _R = rear	150 mm	
		d _S = side	150 mm	
		d _C = ceiling	500 mm	
		d _P = to adjacent combustible materials (e.g. furniture)	800 mm	
		d _F = floor in front	0 mm	
		d _L = side radiation area	0 mm	
		d _B = bottom	0 mm	
		Material type and thickness of the protective insulation material	NPD	
	Hygiene, health, and environmental protection			
	Emissions at nominal heat output at 13% O₂			
	Carbon monoxide (CO)	786 mg/Nm ³		
	Nitrogen (NO _x)	124 mg/Nm ³		
	Organic gaseous carbon (OGC)	40 mg/Nm ³		
	Dust (PM)	28 mg/Nm ³		
	Emissions at reduced heat output at 13% O₂			
	Carbon monoxide (CO)	1114 mg/Nm ³		
	Nitrogen (NO _x)	104 mg/Nm ³		
	Organic gaseous carbon (OGC)	65 mg/Nm ³		
	Dust (PM)	22 mg/Nm ³		
	Safety and accessibility during use			
	Data on installation on a chimney at nominal heat output			
	Temperature at the exhaust pipe	297 °C		
	Minimum delivery pressure	12 Pa		
	Exhaust gas mass flow	7,1 g/s		
	Data on installation on a chimney at reduced heat output			
	Temperature at the exhaust pipe	283 °C		
	Minimum delivery pressure	6 Pa		
	Exhaust gas mass flow	3,9 g/s		
Data on installation on a chimney with regard to fire safety				
Fire safety for installation on the chimney	T400G			
Energy savings and thermal insulation				
Heat output and energy efficiency of the device at nominal heat output				
Space heating capacity	8,0 kW			
Water heating capacity	NPD			
Efficiency	83,4 %			
Heat output and energy efficiency of the device at reduced heat output				
Space heating capacity	4,0 kW			
Water heating capacity	NPD			
Efficiency	83,6 %			
Space heating efficiency				
Annual space heating efficiency at nominal heat output	73 %			
Energy efficiency	Energy-Efficiency-Index (EEI)	111		
	Energy-Efficiency-Class	A+		
Power consumption at nominal heat output	- kW			
Power consumption at reduced heat output	- kW			
Power consumption in standby mode	- kW			
Sustainable use of natural resources				
Ecological sustainability	NPD			
9.)	The performance of the above product corresponds to the declared performance/performances. The above-mentioned manufacturer is solely responsible for preparing the declaration of performance in accordance with Regulation (EU) No. 305/2011.			

Signed on behalf of the manufacturer

Andreas Bloderer / product management
Micheldorf, 20.03.2026