

TECHNICAL DOCUMENTATION

according to commission regulation (EU) 2015/1185 und 2015/1186 Ecodesign

Contact details of the manufacturer

Manufacturer:	RIKA Innovative Ofentechnik GmbH
Contact:	Andreas Bloderer
Address:	Müllerviertel 20
	4563 Micheldorf
	Austria

Details of the device

Model Identifier:	REVO II / REVO II RAO / REVO II PGI 6 kW
Equivalent models:	-
Notified body:	Technische Universität Wien, Getreidemarkt 9/166, 1060 Wien, Austria
Notified body no.:	1746
Test report no.:	PL-19064-2-P
Applied harmonised standards:	EN14785:2006
Other applied standards/technical specifications:	-
Indirect heating functionality:	Nein
Direct heat output:	6,0 kW
Indirect heat output:	-

Characteristics when operating with the preferred fuel

Seasonal space heating energy efficiency ηs:	83,0%
Seasonal space heating energy efficiency RIKATRONIC ηs:	-
Energy Efficiency Index:	125
Energy Efficiency Index RIKATRONIC:	-

Special precautions for assembly, installation or maintenance

Fire protection and safety distances such as distances to combustible building materials must be observed!

 $An adequate \, supply \, of \, combustion \, air \, for \, the \, appliance \, must \, be \, guaranteed \, at \, all \, times. \, Air-suction \, systems \, can \, interfere \, with \, the \, combustion \, air \, supply!$

The flue gas values of the appliance must be observed for the chimney dimensioning!

Characteristics when operating exclusively with the preferred fuel

Heat output			
Nominal heat output	P _{nom}	6,0	kW
Minimum heat output	P _{min}	2,5	kW
Useful efficiency			
Useful efficiency at nominal heat output	η _{th,nom}	93,7	%
Useful efficiency at minimum heat output	η _{th,min}	95,4	%
Auxiliary electricity consumption		•	
At nominal heat output	el _{max}	0,02	kW
At minimum heat output	el _{min}	0,01	kW
In standby mode	el _{SB}	0,003	kW
Permanent pilot flame power requirement		-	
Pilot flame power requirement	P _{pilot}	n.A.	kW

Type of heat output/room temperature control	
single stage heat output, no room temperature control	Yes
two or more manual stages, no room temperature control (**)	No
with mechanic thermostat room temperature control (**)	No
with electronic room temperature control (**)	No
with electronic room temperature control plus day timer (**)	No
with electronic room temperature control plus week timer (**)	No
Room temperature control with presence detection (**)	No
Room temperature control with open window detection (**)	No
with remote control options (**)	No

Details of the fuel

Fuel	Preferred fuel:	Other suitable fuel:	η _s [%]	Space heating emissions at nominal heat output (*)				Space heating emissions at minimum heat output (*)(**)			
				PM	OGC	CO (13% O ₂	NOx	PM ,	OGC ng/Nm³	CO	NO _x
Wood logs, moisture content ≤ 25 %	No	No	-	-	-	-	-	-	-	-	-
Wood logs RIKATRONIC, moisture content ≤ 25 %	No	No	-	-	-	-	-	-	-	-	-
Compressed wood, moisture content < 12 %	Yes	No	83,0	8	3	62	150	-	-	-	-
Other woody biomass	No	No	-	-	-	-	-	-	-	-	-
Non-woody biomass	No	No	-	-	-	-	-	-	-	-	-
Anthracite and dry steam coal	No	No	-	-	-	-	-	-	-	-	-
Hard coke	No	No	-	-	-	-	-	-	-	-	-
Low temperature coke	No	No	-	-	-	-	-	-	-	-	1
Bituminous coal	No	No	-	-	-	-	-	-	-	-	-
Lignite briquettes	No	No	-	-	-	-	-	-	-	-	1
Peat briquettes	No	No	-	-	-	-	-	-	-	-	-
Blended fossil fuel briquettes	No	No	-	-	-	-	-	-	-	-	-
Other fossil fuel	No	No	-	-	-	-	-	-	-	-	=
Blended biomass and fossil fuel briquettes	No	No	-	-	-	-	-	-	-	-	-
Other blend of biomass and solid fuel	No	No	-	-	-	-	-	-	-	-	-

(*) PM = dust, OGC = gaseous organic compounds, CO = carbon monoxide, NOx = nitrous gases (**) Only required when applying correction factors F(2) or F(3)

Signed for and on behalf of the manufacturer by: Andreas Bloderer / product management

Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertel 20
Tel: +43 (0)7582/686-14, Fox DW: -43
www.rika.at

Micheldorf, 25.04.2022