



26

RIKA Innovative Ofentechnik GmbH  
AT-4563 Micheldorf, Müllerviertel 20

regarding EN 16510-2-6:2022 under regulation (EU) 305/2011

**DoP:** 46-CPR-07.2013  
**Notified Body:** 1746  
**Intended use:** Space heating in residential buildings without possible supply of hot water  
**Name:** SWING

**IMPORTANT ASPECTS****MECHANICAL STRENGTH AND STABILITY**

Carrying capacity 25 kg

**FIRE SAFETY**

Safety distance to combustible material	$d_R$ = from the back to combustible materials	150 mm
	$d_S$ = from the sides to flammable materials	150 mm
	$d_C$ = from the top to flammable materials in the ceiling	500 mm
	$d_P$ = from the front to flammable materials	800 mm
	$d_F$ = from the front to flammable materials in the lower front radiation area	0 mm
	$d_L$ = from the front to flammable materials in the lateral front radiation area	0 mm
	$d_B$ = below the floor (without feet) to combustible materials	0 mm

**HYGIENE, HEALTH AND ENVIRONMENTAL PROTECTION**

Emissions at nominal heat output (based on 13% O <sub>2</sub> )	CO	605 mg/Nm <sup>3</sup>
	NOX	106 mg/Nm <sup>3</sup>
	OGC	20 mg/Nm <sup>3</sup>
	PM	20 mg/Nm <sup>3</sup>
Emissions at reduced heat output (based on 13% O <sub>2</sub> )	CO	317 mg/Nm <sup>3</sup>
	NOX	109 mg/Nm <sup>3</sup>
	OGC	9 mg/Nm <sup>3</sup>
	PM	20 mg/Nm <sup>3</sup>

**SAFETY AND ACCESSIBILITY DURING USE**

Data for installation on a chimney at nominal heat output	Temperature at the flue gas connection	265,0 °C
	Minimum conveying pressure	12 Pa
	Flue gas mass flow	6,9 g/S
Data for installation on a chimney at reduced heat output	Temperature at the flue gas connection	281,0 °C
	Minimum conveying pressure	11 Pa
	Flue gas mass flow	6,2 g/S
Data for installation on a chimney regarding fire safety	Class	T400G

**ENERGY SAVINGS AND THERMAL INSULATION**

Heat output and energy efficiency of the appliance at nominal heat output	Room heat output	8,0 kw
	Efficiency	81,3 %
Heat output and energy efficiency of the appliance at reduced heat output	Room heat output	4,0 kw
	Efficiency	80,5 %
Space heating efficiency	Annual space heating efficiency at nominal heat output	71 %
	Energy Efficiency Index (EEI)	108
	Energy efficiency class	A+
	Power consumption at nominal heat output	- kw
	Power consumption at partial load heat output	- kw
	Power consumption in standby mode	- kw

Please read manufacturer's operating instructions carefully before installing



Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Innovative Ofentechnik GmbH  
A-4563 Micheldorf, Müllerviertel 20  
Tel.: +43 (0)7582/686-14, Fax DW: -43

www.rika.at

Micheldorf, 20.03.2026

Place and date of issue